

					Annexure "X"	
Name of work: Waterproofing & repairing work at Rabia Masjid						
S.N	Description of work	Unit	Qty	Rate	Amount	
1	Providing and fixing G.I. pipes complete for the abulation area with G.I. fittings installing.	metre	45.00			
2	Making 80 no of holes of 20mm dia size and fixing GI Socket with welding.	each	80.00			
3	Grading roof for water proofing treatment with Cement mortar 1:3 (1 cement : 3 coarse sand) with waterproofing compound	Cum	0.50			
4	Providing & applying of URP Waterproofing agent in grading, plastering complete as per the direction of Engineer in charge	Ltr	15.00			
5	Chipping the loose surface wherever required, Micro leaning the surfaces with brushing, brooming, washing followed by repairing cracks of the all roof with Cement Mortar admixed with Myltipurpose waterproofing compound. Then applying Priming coat of elastomeric waterproofing compound, laying fiberglassmesh admixed with cement mortar (2ltr waterprofing compound : 1kg cement) then applying 2 coats of elastomatrck (black) rubrized coating (Star Make)	sqm	70.00			
6	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	Sqm	100.00			
7	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : 1 Water thinnable cement primer	sqm	100.00			
8	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete	Sqm	100.00			
9	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour (with two or more coats) Two coats	Sqm	150.00			
10	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : (Two or more coats)	Sqm	50.00			

11	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. With cement mortar 1:4 (1 cement : 4 fine sand)	Sqm	10.00		
12	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	sqm	3.00		
13	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	5.00		
14	Providing and fixing Frosted film on Glass Panes of required size, one side.	Sqm	10.00		
Total Amount i/c GST					

(Signature of the Contractor & Stamp)